



SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Testoval Aluminium Test B**
- **UFI: 6DYU-XT8S-HC01-A7E2**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation:**
Reagent for analysis
EuPCS: PC-TEC-19 Reagents and laboratory chemical
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Gebrüder Heyl
Analystechnik GmbH & Co. KG
Orleansstraße 75 b
D-31135 Hildesheim
Phone +49 (0) 5121 2893390
Fax +49 (0) 5121 2893367
E-mail info@heylanalysis.de
Internet www.heylanalysis.de
- **Further information obtainable from:** product safety department
- **1.4 Emergency telephone number:**
Giftinformationszentrum Nord
Phone +49 (0) 551 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Met. Corr. 1 H290 May be corrosive to metals.
Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labelling:**
thioglycolic acid
sodium metabisulphite
sulphuric acid
- **Hazard statements**
H290 May be corrosive to metals.
H315 Causes skin irritation.
H318 Causes serious eye damage.

(Contd. on page 2)



**Safety data sheet
 according to 1907/2006/EC**

Printing date 03.03.2022

Version number 10 (replaces version 9)

Revision: 03.03.2022

Trade name: Testoval Aluminium Test B

(Contd. of page 1)

Precautionary statements

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P390 Absorb spillage to prevent material damage.

Additional information:

EUH031 Contact with acids liberates toxic gas.

Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms



GHS05

Signal word Danger

Hazard-determining components of labelling:

thioglycolic acid
 sodium metabisulphite
 sulphuric acid

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P390 Absorb spillage to prevent material damage.

2.3 Other hazards

Results of PBT and vPvB assessment

- PBT:** Not applicable.
- vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description:

Mixture of substances listed below with nonhazardous additions according to Regulation (EC) No 1272/2008.

Dangerous components:

CAS: 7681-57-4 EINECS: 231-673-0 Index number: 016-063-00-2 Reg.nr.: 01-2119531326-45	sodium metabisulphite Eye Dam. 1, H318 Acute Tox. 4, H302 EUH031	1 – 2.5%
CAS: 7664-93-9 EINECS: 231-639-5 Index number: 016-020-00-8 Reg.nr.: 01-2119458838-20	sulphuric acid Skin Corr. 1A, H314 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 15 % Skin Irrit. 2; H315: 5 % ≤ C < 15 % Eye Irrit. 2; H319: 5 % ≤ C < 15 %	1 – 2.5%

(Contd. on page 3)



Trade name: Testoval Aluminium Test B

(Contd. of page 2)

CAS: 68-11-1

EINECS: 200-677-4

Index number: 607-090-00-6

Reg.nr.: 01-2119494933-24

thioglycolic acid

Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331

Skin Corr. 1B, H314

1 – 2.5%

· **SVHC** Not applicable.

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· **After swallowing:**

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

Sulphur dioxide (SO₂)

Nitrogen oxides (NO_x)

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

Clean the affected area carefully; suitable cleaners are:

Warm water

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Trade name: Testoval Aluminium Test B

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:** No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

· **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· **Recommended storage temperature:** 15 - 25 °C

· **Storage class:** Storage class 8B: Non-combustible corrosive substances (TRGS 510)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 7681-57-4 sodium metabisulphite

MAK (Germany) | vgl. Abschn. IV

CAS: 7664-93-9 sulphuric acid

AGW (Germany) | Long-term value: 0.1 E mg/m³
 1(I);DFG, EU, Y

CAS: 68-11-1 thioglycolic acid

MAK (Germany) | als Dampf und Aerosol;vgl. Abschn. IIb

Regulatory information

MAK (Germany): MAK- und BAT-Liste

AGW (Germany): TRGS 900

· **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

· **Respiratory protection:**

Use suitable respiratory protective device when aerosol or mist is formed. Filter: Type P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



Trade name: Testoval Aluminium Test B

(Contd. of page 4)

· **Hand protection**



Protective gloves

Wear gloves according to EN 374.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.12 mm

Value for the permeation: Level = 6 (> 480 min)

· **As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.12 mm

Value for the permeation: Level = 6 (> 480 min)

· **Eye/face protection**



Tightly sealed goggles according to EN 166

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Colourless

· **Odour:**

Odourless

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Undetermined.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Flash point:**

Undetermined.

· **Ignition temperature:**

Not determined.

· **Decomposition temperature:**

Not determined.

· **pH (100 g/l) at 20 °C**

5.3

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

(Contd. on page 6)



Safety data sheet
according to 1907/2006/EC

Printing date 03.03.2022

Version number 10 (replaces version 9)

Revision: 03.03.2022

Trade name: Testoval Aluminium Test B

(Contd. of page 5)

· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.09 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	May be corrosive to metals.
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
 To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions**
 Contact with acids releases toxic gases.
 Reacts with alkali (lyes).
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 Nitrogen oxides
 Sulphur oxides (SO_x)

DE_EN

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC

Printing date 03.03.2022

Version number 10 (replaces version 9)

Revision: 03.03.2022

Trade name: Testoval Aluminium Test B

(Contd. of page 6)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

CAS: 7681-57-4 sodium metabisulphite

Oral	LD50	1,420 – 3,200 mg/kg (rat)
Dermal	LD50	> 2,000 mg/kg (rat)
Inhalative	LC50/4 h	5.5 mg/l (rat)

CAS: 7664-93-9 sulphuric acid

Oral	LD50	2,140 mg/kg (rat)
------	------	-------------------

CAS: 68-11-1 thioglycolic acid

Oral	LD50	73 mg/kg (rat)
Dermal	LD50	848 mg/kg (rabbit)
Inhalative	LC50/4 h	1.388 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
 The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 Must not reach sewage water or drainage ditch undiluted or unneutralised.

DE_EN

(Contd. on page 8)



Trade name: Testoval Aluminium Test B

(Contd. of page 7)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packaging:**

· **Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Disposal must be made according to official regulations.

· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1760

· **14.2 UN proper shipping name**

· **ADR**

1760 CORROSIVE LIQUID, N.O.S. (SULPHURIC ACID, THIOGLYCOLIC ACID)

· **IMDG, IATA**

CORROSIVE LIQUID, N.O.S. (SULPHURIC ACID, THIOGLYCOLIC ACID)

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class**

8 Corrosive substances.

· **Label**

8

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Warning: Corrosive substances.

· **Hazard identification number (Kemler code):** 80

· **EMS Number:**

F-A, S-B

· **Segregation groups**

Strong acids

· **Stowage Category**

A

· **Stowage Code**

SW2 Clear of living quarters.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

Void

· **ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

· **Transport category**

3

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC

Printing date 03.03.2022

Version number 10 (replaces version 9)

Revision: 03.03.2022

Trade name: Testoval Aluminium Test B

(Contd. of page 8)

· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (SULPHURIC ACID, THIOGLYCOLIC ACID), 8, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

CAS: 7664-93-9	sulphuric acid	3
----------------	----------------	---

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

CAS: 7664-93-9	sulphuric acid	3
----------------	----------------	---

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· **Technical instructions (air):**

Class	Share in %
I	1 – 2.5

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H301 Toxic if swallowed.

H302 Harmful if swallowed.

(Contd. on page 10)



**Safety data sheet
according to 1907/2006/EC**

Printing date 03.03.2022

Version number 10 (replaces version 9)

Revision: 03.03.2022

Trade name: Testoval Aluminium Test B

(Contd. of page 9)

H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H331 Toxic if inhaled.
EUH031 Contact with acids liberates toxic gas.

- **Department issuing SDS:** product safety department
- **Date of previous version:** 17.04.2020
- **Version number of previous version:** 9
- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Met. Corr. 1: Corrosive to metals – Category 1

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

- *** Data compared to the previous version altered.**